

# DHTML Calendar Widget

Mihai Bazon, <mishoo@infoiasi.ro>

October 29, 2003

calendar version: 0.9.4 “Your favorite time”

\$Id: reference.tex,v 1.11 2003/10/29 00:31:10 mishoo Exp \$

## Contents

<b>1</b>	<b>Overview</b>	<b>2</b>
1.1	How does this thing work? . . . . .	2
1.2	Project files . . . . .	2
1.3	License . . . . .	3
<b>2</b>	<b>Quick startup</b>	<b>3</b>
2.1	Installing a popup calendar . . . . .	3
2.2	Installing a flat calendar . . . . .	4
2.3	Calendar.setup in detail . . . . .	4
<b>3</b>	<b>The Calendar object overview</b>	<b>6</b>
3.1	Creating a calendar . . . . .	7
3.2	Order does matter ;-) . . . . .	7
3.3	Caching the object . . . . .	8
3.4	Callback functions . . . . .	8
<b>4</b>	<b>The Calendar object API reference</b>	<b>9</b>
4.1	Calendar constructor . . . . .	9
4.2	Useful member variables (properties) . . . . .	10
4.3	Public methods . . . . .	10
4.3.1	Calendar.create . . . . .	10
4.3.2	Calendar.callHandler . . . . .	10
4.3.3	Calendar.callCloseHandler . . . . .	11
4.3.4	Calendar.hide . . . . .	11
4.3.5	Calendar.setDateFormat . . . . .	11
4.3.6	Calendar.setTtDateFormat . . . . .	11
4.3.7	Calendar.setDisabledHandler . . . . .	11
4.3.8	Calendar.setDateStatusHandler . . . . .	12
4.3.9	Calendar.show . . . . .	13
4.3.10	Calendar.showAt . . . . .	13
4.3.11	Calendar.showAtElement . . . . .	13
4.3.12	Calendar.setDate . . . . .	14
4.3.13	Calendar.setMondayFirst . . . . .	14
4.3.14	Calendar.parseDate . . . . .	14
4.3.15	Calendar.setRange . . . . .	14
<b>5</b>	<b>Side effects</b>	<b>15</b>
<b>6</b>	<b>Credits</b>	<b>15</b>

# 1 Overview

The DHTML Calendar widget<sup>1</sup> is an (HTML) user interface element that gives end-users a friendly way to select date and time. It works in a web browser. The first versions only provided support for popup calendars, while starting with version 0.9 it also supports “flat” display. A “flat” calendar is a calendar that stays visible in the page all the time. In this mode it could be very useful for “blog” pages and other pages that require the calendar to be always present.

The calendar is compatible with most popular browsers nowadays. While it’s created using web standards and it should generally work with any compliant browser, the following browsers were found to work: Mozilla (the development platform), Netscape 6.0 or better, all other Gecko-based browsers, Internet Explorer 5.0 or better *for Windows*<sup>2</sup>, Opera 7<sup>3</sup> and Konqueror 3.1.2 (with pretty much the same dysfunctions as in Opera).

You can find the latest info and version at the calendar homepage:

<http://dynarch.com/mishoo/calendar.epl>

## 1.1 How does this thing work?

DHTML is not “another kind of HTML”. It’s merely a naming convention. DHTML refers to the combination of HTML, CSS, JavaScript and DOM. DOM (Document Object Model) is a set of interfaces that glues the other three together. In other words, DOM allows dynamic modification of an HTML page through a program. JavaScript is our programming language, since that’s what browsers like. CSS is a way to make it look good ;-). So all this soup is generically known as DHTML.

Using DOM calls, the program dynamically creates a `<table>` element that contains a calendar for the given date and then inserts it in the document body. Then it shows this table at a specified position. Usually the position is related to some element in which the date needs to be displayed/entered, such as an input field.

By assigning a certain CSS class to the table we can control the look of the calendar through an external CSS file; therefore, in order to change the colors, backgrounds, rollover effects and other stuff, you can only change a CSS file—modification of the program itself is not necessary.

## 1.2 Project files

Here’s a description of the project files, excluding documentation and example files.

- the main program file (`calendar.js`). This defines all the logic behind the calendar widget.
- the CSS files (`calendar-*.css`). Loading one of them is necessary in order to see the calendar as intended.
- the language definition files (`lang/calendar-*.js`). They are plain JavaScript files that contain all texts that are displayed by the calendar. Loading one of them is necessary.
- helper functions for quick setup of the calendar (`calendar-setup.js`). You can do fine without it, but starting with version 0.9.3 this is the recommended way to setup a calendar.

---

<sup>1</sup>by the term “widget” I understand a single element of user interface. But that’s in Linux world. For those that did lots of Windows programming the term “control” might be more familiar

<sup>2</sup>people report that the calendar does not work with IE5/Mac. I don’t have access to a Macintosh, therefore—sorry—I can’t fix it.

<sup>3</sup>under Opera 7 the calendar still lacks some functionality, such as keyboard navigation; also Opera doesn’t seem to allow disabling text selection when one drags the mouse on the page; despite all that, the calendar is still highly functional under Opera 7 and looks as good as in other supported browsers.

## 1.3 License

© Mihai Bazon, 2002 – 2003, <mishoo@infoiasi.ro>  
<http://dynarch.com/mishoo/>

The calendar is released under the [GNU Lesser General Public License](#). You can [read the entire license text here](#).

## 2 Quick startup

Installing the calendar used to be quite a task until version 0.9.3. Starting with 0.9.3 I have included the file `calendar-setup.js` whose goal is to assist you to setup a popup or flat calendar in minutes. You are encouraged to modify this file and *not* `calendar.js` if you need extra customization, but you're on your own.

First you have to include the needed scripts and style-sheet. Make sure you do this in your document's `<head>` section, also make sure you put the correct paths to the scripts.

```
<style type="text/css">@import url(calendar-win2k-1.css)</style>
<script type="text/javascript" src="calendar.js"></script>
<script type="text/javascript" src="lang/calendar-en.js"></script>
<script type="text/javascript" src="calendar-setup.js"></script>
```

### 2.1 Installing a popup calendar

Now suppose you have the following HTML:

```
<form ...>
  <input type="text" id="data" name="data" />
  <button id="trigger">...</button>
</form>
```

You want the button to popup a calendar widget when clicked? Just insert the following code immediately *after* the HTML form:

```
<script type="text/javascript">
  Calendar.setup(
    {
      inputField  : "data",      // ID of the input field
      ifFormat    : "M d, y",    // the date format
      button      : "trigger"    // ID of the button
    }
  );
</script>
```

The `Calendar.setup` function, defined in `calendar-setup.js` takes care of “patching” the button to display a calendar when clicked. The calendar is by default in single-click mode and linked with the given input field, so that when the end-user selects a date it will update the input field with the date in the given format and close the calendar. If you are a long-term user of the calendar you probably remember that for doing this you needed to write a couple functions and add an “onclick” handler for the button by hand.

By looking at the example above we can see that the function `Calendar.setup` receives only one parameter: a JavaScript object. Further, that object can have lots of properties that tell to the setup function how would we like to have the calendar. For instance, if we would like a calendar that closes at double-click instead of single-click we would also include the following: `singleClick:false`.

For a list of all supported parameters please see the section [2.3](#).

## 2.2 Installing a flat calendar

Here's how to configure a flat calendar, using the same `Calendar.setup` function. First, you should have an empty element with an ID. This element will act as a container for the calendar. It can be any block-level element, such as `DIV`, `TABLE`, etc. We will use a `DIV` in this example.

```
<div id="calendar-container"></div>
```

Then there is the JavaScript code that sets up the calendar into the “calendar-container” `DIV`. The code can occur anywhere in HTML *after* the `DIV` element.

```
<script type="text/javascript">
function dateChanged(calendar) {
    // Beware that this function is called even if the end-user only
    // changed the month/year. In order to determine if a date was
    // clicked you can use the dateClicked property of the calendar:
    if (calendar.dateClicked) {
        // OK, a date was clicked, redirect to /yyyy/mm/dd/index.php
        var y = calendar.date.getFullYear();
        var m = calendar.date.getMonth();      // integer, 0..11
        var d = calendar.date.getDate();       // integer, 1..31
        // redirect...
        window.location = "/" + y + "/" + m + "/" + d + "/index.php";
    }
};

Calendar.setup(
{
    flat          : "calendar-container", // ID of the parent element
    flatCallback : dateChanged           // our callback function
}
);
</script>
```

## 2.3 Calendar.setup in detail

Following there is the complete list of properties interpreted by `Calendar.setup`. All of them have default values, so you can pass only those which you would like to customize. Anyway, you *must* pass at least one of `inputField`, `displayArea` or `button`, for a popup calendar, or `flat` for a flat calendar. Otherwise you will get a warning message saying that there's nothing to setup.

property	type	description	default
<code>inputField</code>	string	The ID of your input field.	null
<code>displayArea</code>	string	This is the ID of a <code>&lt;span&gt;</code> , <code>&lt;div&gt;</code> , or any other element that you would like to use to display the current date. This is generally useful only if the input field is hidden, as an area to display the date.	null
<code>button</code>	string	The ID of the calendar “trigger”. This is an element (ordinarily a button or an image) that will dispatch a certain event (usually “click”) to the function that creates and displays the calendar.	null

property	type	description	default
<b>eventName</b>	string	The name of the event that will trigger the calendar. The name should be without the “on” prefix, such as “click” instead of “onclick”. Virtually all users will want to let this have the default value (“click”). Anyway, it could be useful if, say, you want the calendar to appear when the input field is focused and have no trigger button (in this case use “focus” as the event name).	“click”
<b>ifFormat</b>	string	The format string that will be used to enter the date in the input field. This format will be honored even if the input field is hidden.	“%Y/%m/%d”
<b>daFormat</b>	string	Format of the date displayed in the displayArea (if specified).	“%Y/%m/%d”
<b>singleClick</b>	boolean	Whether the calendar is in “single-click mode” or “double-click mode”. If true (the default) the calendar will be created in single-click mode.	true
<b>disableFunc</b>	function	A function that receives a JS Date object. It should return <b>true</b> if that date has to be disabled, <b>false</b> otherwise. <b>DEPRECATED (see below)</b> .	null
<b>dateStatusFunc</b>	function	A function that receives a JS Date object and returns a boolean or a string. This function allows one to set a certain CSS class to some date, therefore making it look different. If it returns <b>true</b> then the date will be disabled. If it returns <b>false</b> nothing special happens with the given date. If it returns a string then that will be taken as a CSS class and appended to the date element. If this string is “disabled” then the date is also disabled (therefore is like returning <b>true</b> ). For more information please also refer to section 4.3.8.	null
<b>mondayFirst</b>	boolean	If <b>true</b> (default) then the calendar will display with Monday being the first day of week. If <b>false</b> then Sunday will be the first day of week. This has changed from default <b>false</b> to default <b>true</b> because the ISO 8601 defines week as starting Monday and this definition is used for computing the week number.	true
<b>weekNumbers</b>	boolean	If “true” then the calendar will display week numbers.	true
<b>align</b>	string	Alignment of the calendar, relative to the reference element. The reference element is dynamically chosen like this: if a displayArea is specified then it will be the reference element. Otherwise, the input field is the reference element. For the meaning of the alignment characters please see section 4.3.11.	“Bl”
<b>range</b>	array	An array having exactly 2 elements, integers. (!) The first [0] element is the minimum year that is available, and the second [1] element is the maximum year that the calendar will allow.	[1900, 2999]
<b>flat</b>	string	If you want a flat calendar, pass the ID of the parent object in this property. If not, pass <b>null</b> here (or nothing at all as <b>null</b> is the default value).	null

property	type	description	default
<code>flatCallback</code>	function	You should provide this function if the calendar is flat. It will be called when the date in the calendar is changed with a reference to the calendar object. See section <a href="#">2.2</a> for an example of how to setup a flat calendar.	null
<code>onSelect</code>	function	If you provide a function handler here then you have to manage the “click-on-date” event by yourself. Look in the <code>calendar-setup.js</code> and take as an example the <code>onSelect</code> handler that you can see there.	null
<code>onClose</code>	function	This handler will be called when the calendar needs to close. You don’t need to provide one, but if you do it’s your responsibility to hide/destroy the calendar. You’re on your own. Check the <code>calendar-setup.js</code> file for an example.	null
<code>onUpdate</code>	function	If you supply a function handler here, it will be called right after the target field is updated with a new date. You can use this to chain 2 calendars, for instance to setup a default date in the second just after a date was selected in the first.	null
<code>date</code>	date	This allows you to setup an initial date where the calendar will be positioned to. If absent then the calendar will open to the today date.	null
<code>showsTime</code>	boolean	If this is set to <code>true</code> then the calendar will also allow time selection.	false
<code>timeFormat</code>	string	Set this to “12” or “24” to configure the way that the calendar will display time.	“24”

### 3 The Calendar object overview

Basically you should be able to setup the calendar with the function presented in the previous section. However, if for some reason `Calendar.setup` doesn’t provide all the functionality that you need and you want to tweak into the process of creating and configuring the calendar “by hand”, then this section is the way to go.

The file `calendar.js` implements the functionality of the calendar. All (well, almost all) functions and variables are embedded in the JavaScript object “Calendar”.

You can instantiate a `Calendar` object by calling the constructor, like this: `var cal = new Calendar(...)`. We will discuss the parameters later. After creating the object, the variable `cal` will contain a reference to it. You can use this reference to access further options of the calendar, for instance:

```
cal.weekNumbers = false; // do not display week numbers
cal.showsTime = true;    // include a time selector
cal.setDateFormat("%Y.%m.%d %H:%M"); // set this format: 2003.12.31 23:59
cal.setDisabledHandler(function(date, year, month, day) {
    // verify date and return true if it has to be disabled
    // ‘date’ is a JS Date object, but if you only need the
    // year, month and/or day you can get them separately as
    // next 3 parameters, as you can see in the declaration
    if (year == 2004) {
        // disable all dates from 2004
        return true;
    }
    return false;
});
```

etc. Prior to version 0.9.3 this was the only way to configure it. The `Calendar.setup`

function, documented in section 2, basically does the same things (actually more) in order to setup the calendar, based on the parameters that you provided.

### 3.1 Creating a calendar

The calendar is created by following some steps (even the function `Calendar.setup`, described in section 2, does the same). While you can skip optional (marked “opt”) steps if you’re happy with the defaults, please respect the order below.

1. *Instantiate* a `Calendar` object. Details about this in section 4.1.
- opt Set the `weekNumbers` property to `false` if you don’t want the calendar to display week numbers.
- opt Set the `showsTime` property to `true` if you want the calendar to also provide a time selector.
- opt Set the `time24` property to `false` if you want the time selector to be in 12-hour format. Default is 24-hour format. This property only has effect if you also set `showsTime` to `true`.
- opt Set the range of years available for selection (see section 4.3.15). The default range is [1970..2050].
- opt Set the `getDateStatus` property. You should pass here a function that receives a JavaScript `Date` object and returns `true` if the given date should be disabled, `false` otherwise (details in section 4.3.7).
- opt Set a date format. Your handler function, passed to the calendar constructor, will be called when a date is selected with a reference to the calendar and a date string in this format.
2. *Create* the HTML elements related to the calendar. This step practically puts the calendar in your HTML page. You simply call `Calendar.create()`. You can give an optional parameter if you wanna create a flat calendar (details in section 4.3.1).
- opt Initialize the calendar to a certain date, for instance from the input field.
3. Show the calendar (details in section 4.3.9).

### 3.2 Order does matter ;-)

As you could see in the previous section, there are more steps to be followed in order to setup the calendar. This happens because there are two different things that need to be accomplished: first there is the JavaScript object, that is created with `new Calendar(...)`. Secondly there are the HTML elements that actually lets you see and manipulate the calendar.

[ Those that did UI<sup>4</sup> programming, no matter in what language and on what platform, may be familiar with this concept. First there is the object in memory that lets you manipulate the UI element, and secondly there is the UI element (known as “control”, “window”, “widget”, etc.), also in memory but you don’t usually access it directly. ]

By instantiating the calendar we create the JavaScript object. It lets us configure some properties and it also knows how to create the UI element (the HTML elements actually) that will eventually be what the end-user sees on screen. Creation of the HTML element is accomplished by the function `Calendar.create`. It knows how to create popup or flat calendars. This function is described in section 4.3.1.

Some properties need to be set prior to creating the HTML elements, because otherwise they wouldn’t have any effect. Such a property is `weekNumbers`—it has the default value “true”, and if you don’t want the calendar to display the week numbers you have to set it to false. If, however, you do that *after* calling `Calendar.create` the calendar would still

---

<sup>4</sup>user interface

display the week numbers, because the HTML elements are already created (including the `<td>`-s in the `<table>` element that should contain the week numbers). For this reason the order of the steps above is important.

Another example is when you want to show the calendar. The “create” function does create the HTML elements, but they are initially hidden (have the style “display: none”) unless the calendar is a flat calendar that should be always visible in the page. Obviously, the `Calendar.show` function should be called *after* calling `Calendar.create`.

### 3.3 Caching the object

Suppose the end-user has popped up a calendar and selects a date. The calendar then closes. What really happens now?

There are two approaches. The first (used in very old versions of the calendar) was to drop completely the `Calendar` object and when the end-user pops up the calendar again to create another one. This approach is bad for more reasons:

- creating the JavaScript object and HTML elements is time-consuming
- we may loose some end-user preferences (i.e. he might prefer to have Monday for the first day of week and probably already clicked it the first time when the calendar was opened, but now he has to do it again)

The second approach, implemented by the `Calendar.setup` function, is to cache the JavaScript object. It does this by checking the global variable `window.calendar` and if it is not null it assumes it is the created `Calendar` object. When the end-user closes the calendar, our code will only call “hide” on it, therefore keeping the JavaScript object and the HTML elements in place.

**CAVEAT:** Since time selection support was introduced, this “object caching” mechanism has the following drawback: if you once created the calendar with the time selection support, then other items that may not require this functionality will still get a calendar with the time selection support enabled. And reciprocal. ;-) Hopefully this will be corrected in a later version, but for now it doesn’t seem such a big problem.

### 3.4 Callback functions

You might rightfully wonder how is the calendar related to the input field? Who tells it that it has to update *that* input field when a date is selected, or that it has to jump to *that* URL when a date is clicked in flat mode?

All this magic is done through callback functions. The calendar doesn’t know anything about the existence of an input field, nor does it know where to redirect the browser when a date is clicked in flat mode. It just calls your callback when a particular event is happening, and you’re responsible to handle it from there. For a general purpose library I think this is the best model of making a truly reusable thing.

The calendar supports the following user callbacks:

`onSelect` — this gets called when the end-user changes the date in the calendar. Documented in section 4.1.

`onClose` — this gets called when the calendar should close. It’s user’s responsibility to close the calendar. Details in section 4.1.

`getDateStatus` — this function gets called for any day in a month, just before displaying the month. It is called with a JavaScript `Date` object and should return `true` if that date should be disabled, false if it’s an ordinary date and no action should be taken, or it can return a string in which case the returned value will be appended to the element’s CSS class (this way it provides a powerful way to make some dates “special”, i.e. highlight them differently). Details in section 4.3.8.



## 4 The Calendar object API reference

### 4.1 Calendar constructor

Synopsis:

```
var calendar = Calendar(mondayFirst, date, onSelect, onClose);
```

Parameters are as follows:

`mondayFirst` — boolean, if it's `true` the calendar will have Monday as first day of week, if `false` weeks start on Sunday.

`date` — a JavaScript Date object or `null`. If `null` is passed then the calendar will default to today date. Otherwise it will initialize on the given date.

`onSelect` — your callback for the “onChange” event. See above.

`onClose` — your callback for the “onClose” event. See above.

#### The onSelect event

Here is a typical implementation of this function:

```
function onSelect(calendar, date) {  
    var input_field = document.getElementById("date");  
    input_field.value = date;  
};
```

`date` is in the format selected with `calendar.setDateFormat` (see section 4.3.5). This code simply updates the input field. If you want the calendar to be in single-click mode then you should also close the calendar after you updated the input field, so we come to the following version:

```
function onSelect(calendar, date) {  
    var input_field = document.getElementById("date");  
    input_field.value = date;  
    if (calendar.dateClicked) {  
        calendar.callCloseHandler(); // this calls "onClose" (see above)  
    }  
};
```

Note that we checked the member variable `dateClicked` and only hide the calendar if it's `true`. If this variable is `false` it means that no date was actually selected, but the user only changed the month/year using the navigation buttons or the menus. We don't want to hide the calendar in that case.

#### The onClose event

This event is triggered when the calendar should close. It should hide or destroy the calendar object—the calendar itself just triggers the event, but it won't close itself.

A typical implementation of this function is the following:

```
function onClose(calendar) {  
    calendar.hide();  
    // or calendar.destroy();  
};
```

## 4.2 Useful member variables (properties)

After creating the Calendar object you can access the following properties:

- **date** — is a JavaScript `Date` object. It will always reflect the date shown in the calendar (yes, even if the calendar is hidden).
- **isPopup** — if this is `true` then the current Calendar object is a popup calendar. Otherwise (`false`) we have a flat calendar. This variable is set from `Calendar.create` and has no meaning before this function was called.
- **dateClicked** — particularly useful in the `onSelect` handler, this variable tells us if a date was really clicked. That's because the `onSelect` handler is called even if the end-user only changed the month/year but did not select a date. We don't want to close the calendar in that case.
- **weekNumbers** — if `true` (default) then the calendar displays week numbers. If you don't want week numbers you have to set this variable to `false` *before* calling `Calendar.create`.
- **showsTime** — if you set this to `true` (it is `false` by default) then the calendar will also include a time selector.
- **time24** — if you set this to `false` then the time selector will be in 12-hour format. It is in 24-hour format by default.
- **mondayFirst** — if `true` then the calendar uses Monday as first day of week, otherwise Sunday. This variable is set from constructor, but you still have a chance to modify it *before* calling `Calendar.create`.

There are lots of other member variables, but one should access them only through member functions so I won't document them here.

## 4.3 Public methods

### 4.3.1 `Calendar.create`

This function creates the afferent HTML elements that are needed to display the calendar. You should call it after setting the calendar properties. Synopsis:

```
calendar.create(); // creates a popup calendar
// -- or --
calendar.create(document.getElementById(parent_id)); // makes a flat calendar
```

It can create a popup calendar or a flat calendar. If the “parent” argument is present (it should be a *reference*—not ID—to an HTML element) then a flat calendar is created and it is inserted in the given element.

At any moment, given a reference to a calendar object, we can inspect if it's a popup or a flat calendar by checking the boolean member variable `isPopup`:

```
if (calendar.isPopup) {
    // this is a popup calendar
} else {
    // this is a flat calendar
}
```

### 4.3.2 `Calendar.callHandler`

This function calls the first user callback (the `onSelect` handler) with the required parameters.

#### 4.3.3 `Calendar.callCloseHandler`

This function calls the second user callback (the `onClose` handler). It's useful when you want to have a “single-click” calendar—just call this in your `onSelect` handler, if a date was clicked.

#### 4.3.4 `Calendar.hide`

Call this function to hide the calendar. The calendar object and HTML elements will not be destroyed, thus you can later call one of the `show` functions on the same element.

#### 4.3.5 `Calendar.setDateFormat`

This function configures the format in which the calendar reports the date to your “onSelect” handler. Call it like this:

```
calendar.setDateFormat("%y/%m/%d");
```

As you can see, it receives only one parameter, the required format. The magic characters are the following:

%a	abbreviated weekday name
%A	full weekday name
%b	abbreviated month name
%B	full month name
%C	century number
%d	the day of the month ( 00 .. 31 )
%e	the day of the month ( 0 .. 31 )
%H	hour ( 00 .. 23 )
%I	hour ( 01 .. 12 )
%j	day of the year ( 000 .. 366 )
%k	hour ( 0 .. 23 )
%l	hour ( 1 .. 12 )
%m	month ( 01 .. 12 )
%M	minute ( 00 .. 59 )
%n	a newline character
%p	“PM” or “AM”
%P	“pm” or “am”
%S	second ( 00 .. 59 )
%s	number of seconds since Epoch (since Jan 01 1970 00:00:00 UTC)
%t	a tab character
%U, %W, %V	the week number <sup>5</sup>
%u	the day of the week ( 1 .. 7, 1 = MON )
%w	the day of the week ( 0 .. 6, 0 = SUN )
%y	year without the century ( 00 .. 99 )
%Y	year including the century ( ex. 1979 )
%%	a literal % character

#### 4.3.6 `Calendar.setTtDateFormat`

Has the same prototype as `Calendar.setDateFormat`, but refers to the format of the date displayed in the “status bar” when the mouse is over some date.

#### 4.3.7 `Calendar.setDisabledHandler`

This function allows you to specify a callback function that checks if a certain date must be disabled by the calendar. You are responsible to write the callback function. Synopsis:

```
function disallowDate(date) {
  // date is a JS Date object
  if ( date.getFullYear() == 2003 &&
        date.getMonth()    == 6 /* July, it's zero-based */ &&
        date.getDate()     == 5 ) {
    return true; // disable July 5 2003
  }
  return false; // enable other dates
};

calendar.setDisabledHandler(disallowDate);
```

If you change this function in “real-time”, meaning, without creating a new calendar, then you have to call `calendar.refresh()` to make it redisplay the month and take into account the new disabledHandler. `Calendar.setup` does this, so you have no such trouble with it.

Note that `disallowDate` should be very fast, as it is called for each date in the month. Thus, it gets called, say, 30 times before displaying the calendar, and 30 times when the month is changed. Tests I’ve done so far show that it’s still good, but in the future I might switch it to a different design (for instance, to call it once per month and to return an array of dates that must be disabled).

This function should be considered deprecated in the favor of `Calendar.setDateStatusHandler`, described below.

#### 4.3.8 Calendar.setDateStatusHandler

This function obsoletes `Calendar.setDisabledHandler`. You call it with a function parameter, but this function can return a boolean *or a string*. If the return value is a boolean (`true` or `false`) then it behaves just like `setDisabledHandler`, therefore disabling the date if the return value is `true`.

If the returned value is a string then the given date will gain an additional CSS class, namely the returned value. You can use this to highlight some dates in some way. Note that you are responsible for defining the CSS class that you return. If you return the string “disabled” then that date will be disabled, just as if you returned `true`.

Here is a simple scenario that shows what you can do with this function. The following should be present in some of your styles, or in the document head in a `STYLE` tag (but put it *after* the place where the calendar styles were loaded):

```
.special { background-color: #000; color: #fff; }
```

And you would use the following code before calling `Calendar.create()`:

```
// this table holds your special days, so that we can automatize
// things a bit:
var SPECIAL_DAYS = {
  0 : [ 13, 24 ],           // special days in January
  2 : [ 1, 6, 8, 12, 18 ],  // special days in March
  8 : [ 21, 11 ],          // special days in September
  11 : [ 25, 28 ]          // special days in December
};

// this function returns true if the passed date is special
function dateIsSpecial(year, month, day) {
  var m = SPECIAL_DAYS[month];
  if (!m) return false;
  for (var i in m) if (m[i] == day) return true;
  return false;
}
```

```
// this is the actual date status handler. Note that it receives the
// date object as well as separate values of year, month and date, for
// your confort.
function dateStatusHandler(date, y, m, d) {
    if (dateIsSpecial(y, m, d)) return "special";
    else return false;
    // return true above if you want to disable other dates
}

// configure it to the calendar
calendar.setDateStatusHandler(dateStatusHandler);
```

The above code adds the “special” class name to some dates that are defined in the SPECIAL\_DAYS table. Other dates will simply be displayed as default, enabled.

#### 4.3.9 Calendar.show

Call this function to show the calendar. It basically sets the CSS “display” property to “block”. It doesn’t modify the calendar position.

This function only makes sense when the calendar is in popup mode.

#### 4.3.10 Calendar.showAt

Call this to show the calendar at a certain (x, y) position. Prototype:

```
calendar.showAt(x, y);
```

The parameters are absolute coordinates relative to the top left corner *of the page*, thus they are *page* coordinates not screen coordinates.

After setting the given coordinates it calls Calendar.show. This function only makes sense when the calendar is in popup mode.

#### 4.3.11 Calendar.showAtElement

This function is useful if you want to display the calendar near some element. You call it like this:

```
calendar.showAtElement(element, align);
```

where element is a reference to your element (for instance it can be the input field that displays the date) and align is an optional parameter, of type string, containing one or two characters. For instance, if you pass “Br” as align, the calendar will appear *below* the element and with its right margin continuing the element’s right margin.

As stated above, align may contain one or two characters. The first character dictates the vertical alignment, relative to the element, and the second character dictates the horizontal alignment. If the second character is missing it will be assumed “l” (the left margin of the calendar will be at the same horizontal position as the left margin of the element).

The characters given for the align parameters are case sensitive. This function only makes sense when the calendar is in popup mode. After computing the position it uses Calendar.showAt to display the calendar there.

**Vertical alignment** The first character in “align” can take one of the following values:

- T — completely above the reference element (bottom margin of the calendar aligned to the top margin of the element).
- t — above the element but may overlap it (bottom margin of the calendar aligned to the bottom margin of the element).

- **c** — the calendar displays vertically centered to the reference element. It might overlap it (that depends on the horizontal alignment).
- **b** — below the element but may overlap it (top margin of the calendar aligned to the top margin of the element).
- **B** — completely below the element (top margin of the calendar aligned to the bottom margin of the element).

**Horizontal alignment** The second character in “align” can take one of the following values:

- **L** — completely to the left of the reference element (right margin of the calendar aligned to the left margin of the element).
- **l** — to the left of the element but may overlap it (left margin of the calendar aligned to the left margin of the element).
- **c** — horizontally centered to the element. Might overlap it, depending on the vertical alignment.
- **r** — to the right of the element but may overlap it (right margin of the calendar aligned to the right margin of the element).
- **R** — completely to the right of the element (left margin of the calendar aligned to the right margin of the element).

**Default values** If the “align” parameter is missing the calendar will choose “B1”. This resembles the behavior of older versions (prior to 0.9.3) which did not support custom alignment.

#### 4.3.12 `Calendar.setDate`

Receives a JavaScript `Date` object. Sets the given date in the calendar. If the calendar is visible the new date is displayed immediately.

```
calendar.setDate(new Date()); // go today
```

#### 4.3.13 `Calendar.setMondayFirst`

Changes the first day of week. If the parameter is `true` then Monday will be the first day of week, otherwise Sunday.

```
calendar.setMondayFirst(false); // use Sunday
```

#### 4.3.14 `Calendar.parseDate`

Use this function to parse a date given as string and to move the calendar to that date.

The algorithm tries to parse the date according to the format that was previously set with `Calendar.setDateFormat`; if that fails, it still tries to get some valid date out of it (it doesn’t read your thoughts, though).

```
calendar.parseDate("2003/07/06");
```

#### 4.3.15 `Calendar.setRange`

Sets the range of years that are allowed in the calendar. Synopsis:

```
calendar.setRange(1970, 2050);
```

## 5 Side effects

The calendar code was intentionally embedded in an object to make it have as less as possible side effects. However, there are some—not harmful, after all. Here is a list of side effects; you can count they already happened after `calendar.js` was loaded.

1. The global variable `window.calendar` will be set to null. This variable is used by the calendar code, especially when doing drag & drop for moving the calendar. In the future I might get rid of it, but for now it didn't harm anyone.
2. The JavaScript `Date` object is modified. We add some properties and functions that are very useful to our calendar. It made more sense to add them directly to the `Date` object than to the calendar itself. Complete list:

- (a) `Date._MD = new Array(31,28,31,30,31,30,31,31,30,31,30,31);`
- (b) `Date.SECOND = 1000 /* milliseconds */;`
- (c) `Date.MINUTE = 60 * Date.SECOND;`
- (d) `Date.HOUR = 60 * Date.MINUTE;`
- (e) `Date.DAY = 24 * Date.HOUR;`
- (f) `Date.WEEK = 7 * Date.DAY;`
- (g) `Date.prototype.getMonthDays(month)` — returns the number of days of the given month, or of the current date object if no month was given.
- (h) `Date.prototype.getWeekNumber()` — returns the week number of the date in the current object.
- (i) `Date.prototype.equalsTo(other_date)` — compare the current date object with `other_date` and returns `true` if the dates are equal. *It ignores time.*
- (j) `Date.prototype.print(format)` — returns a string with the current date object represented in the given format. It implements the format specified in section 4.3.5.

## 6 Credits

The following people either sponsored, donated money to the project or bought commercial licenses (listed in reverse chronological order). Your name could be here too! If you wish to sponsor the project (for instance request a feature and pay me for implementing it) or donate some money please *please* contact me at [mishoo@infoiasi.ro](mailto:mishoo@infoiasi.ro).

- Himanshukumar Shah
- Seyhan Ersoy (<http://www.oocgi.com>)
- Jon Stokkeland (<http://www.sauen.com>)

**Thank you!**  
— [mishoo@infoiasi.ro](mailto:mishoo@infoiasi.ro)